



MK Diamond Products, Inc.

CONCRETE SAWS

MK-24 Series

MK-20 Series

MK-1813H Saw

MK-1600 Series

CX-3® Saw

SRX-150 Saw

SRX-2000 Saw



1315 Storm Parkway, Torrance, CA 90501, USA
Tel: 1.800.421.5830, 310.539.5221 • Fax: 310.539.5158
mkdiamond.com • customer_service@mkdiamond.com





MK-2420HSP



MK-2425KSP

MK-24 Series Self-Propelled Concrete Saw

MK-24 Series of concrete saws combine innovation and engineering to produce one of the lightest, midsize self-propelled concrete saws available. Key to the design is the featured box frame and channel that produces a rigid frame, which helps reduce sawing-induced vibrations. Engine weight is evenly distributed over the blade shaft for added stability and tracking. Depth control assembly is engineered for smooth, controlled blade insertion. One-year limited warranty.

| | | | |
|--------------------|-------------------------|-------------------|-------------------|
| Arbor Size | 1" (25 mm) | | |
| L x W x H (inches) | 49" x 25" x 45" | | |
| L x W x H (mm) | 1,245 x 635 x 1,143 | | |
| Includes | Lifting Bail | | |
| Model | MK-2420HSP | MK-2424HSP | MK-2425KSP |
| Engine | Honda (Gas) | Honda (Gas) | Kohler (Propane) |
| Starter | Electric | Electric | Electric |
| Power | GX630 V-Twin* | GX690 V-Twin* | CH730LPG* |
| Blade Capacity | 24" (610 mm) | 24" (610 mm) | 24" (610 mm) |
| Depth of Cut | 9-5/8" (244 mm) | 9-5/8" (244 mm) | 9-5/8" (244 mm) |
| Weight | 398 lbs. (181 kg) | 404 lbs. (183 kg) | 425 lbs. (193 kg) |
| Part# | 170954 | 170955 | 170957 |
| Optional | 6.5 Gallon Water Tank** | Water Pump Kit | |
| Part# | 157852 | 172896 | |



Hinged blade guard for easy inspection & blade changes



Blade guard uses ride-on-the-blade water tubes for superior water delivery & blade cooling



Control panel allows for quick access & ease of operation

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.

**Not available for propane model
Blade not included.

Recommended Diamond Blades

MK-505 Supreme Grade Cured Concrete

| Size | Part # |
|------|--------|
| 24" | 135319 |



MK-615W Premium Grade Asphalt over Concrete

| Size | Part # |
|------|--------|
| 24" | 150233 |



MK-710W Supreme Grade Asphalt

| Size | Part # |
|------|--------|
| 24" | 151298 |



MK-7501 Professional Cured Concrete

| Size | Part # |
|------|--------|
| 24" | 153305 |





MK-2013HE

MK-20 SERIES Self-Propelled Concrete Saw

MK-20 Series of concrete saws combine innovation and engineering to produce one of the lightest, midsize self-propelled concrete saws available. Key to the design is the featured box frame and channel that produces a rigid frame, which helps reduce sawing-induced vibrations. Engine weight is evenly distributed over the blade shaft for added stability and tracking. Depth control assembly is engineered for smooth, controlled blade insertion. One-year limited warranty.

| | | |
|--------------------|-----------------------|-------------------|
| Arbor Size | 1" (25 mm) | |
| L x W x H (inches) | 46" x 26" x 37" | |
| L x W x H (mm) | 1,168 x 660 x 940 | |
| Includes | • Lifting Bail | |
| Model | MK-2013HE | MK-2013HSP |
| Engine | Honda (Gas) | Honda (Gas) |
| Starter | Electric | Pull |
| Power | GX390 Cyclone* | GX390 Cyclone* |
| Blade Capacity | 18" (457 mm) | 18" (457 mm) |
| Depth of Cut | 6-5/8" (168 mm) | 6-5/8" (168 mm) |
| Weight | 290 lbs. (132 kg) | 290 lbs. (132 kg) |
| Part# | 155714 | 156499 |
| Optional | 6.5 Gallon Water Tank | Water Pump Kit |
| Part# | 157852 | 172896 |

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating. Blade not included.



Cast aluminum hinged blade guard



Blade guard mounts on either left- or right-hand side of saw and cuts within 2" of wall or curb



Easy to use control panel, includes built-in tach/hour meter.

Recommended Diamond Blades

MK-505 Supreme Grade Cured Concrete

| Size | Part # |
|------|--------|
| 16" | 139238 |
| 18" | 129072 |



MK-615W Premium Grade Asphalt over Concrete

| Size | Part # |
|------|--------|
| 16" | 150231 |
| 18" | 150232 |



MK-710W Supreme Grade Asphalt

| Size | Part # |
|------|--------|
| 16" | 152646 |
| 18" | 139089 |



MK-762DMX Supreme Grade General Purpose/Concrete

| Size | Part # |
|------|--------|
| 16" | 161294 |
| 18" | 161295 |





MK-1813H 18" Walk-Behind Gas Concrete Saw

The MK-1800 Concrete Saw is designed for wet or dry, general application sawing. The heavy-duty frame is made from hot-rolled steel providing maximum durability and the reinforced box steel construction provides balanced weight distribution. The ergonomic vibration dampening handlebars reduce operator fatigue. The depth control assembly allows the blade to be raised and lowered to the desired cutting depth easily. The Micro-V 20J belt provides maximum power transmission to the blade shaft. One year limited warranty.

| | |
|---------------------------|---|
| Model | MK-1813H |
| Engine | Honda (Gas) |
| Power | GX390 Cyclone* |
| Blade Capacity | 18" (457 mm) |
| Depth of Cut | 6-5/8" (168 mm) |
| Arbor Size | 1" (25 mm) |
| L x W x H (inches) | 48" x 20" x 41" |
| L x W x H (mm) | 1,219 x 508 x 1,041 |
| Weight | 253 lbs. (115 kg) |
| Includes | <ul style="list-style-type: none"> • Built-in Depth Gauge • 6 Gallon Water Tank • Lifting Bail |
| Part# | 172739 |

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.

Blade not included.



Adjustable height handlebar for operator comfort



Ride-on-the-blade water distribution provides water to both sides of the blade for optimum cooling



6 gallon Water Tank with city water control valve/hook up



MK-1613H Standard



MK-1613B Premium

MK-1600 Series Walk-Behind Concrete Saws

All MK-1600 Series walk-behind concrete saws feature a one-piece box construction chassis made from 3/16" hot-rolled steel that will not flex during operation. Powder-coated chassis resists peeling and corrosion. The blade cuts within 2" of wall or curb. Premium saws include built-in depth gauge, lifting bail and a tach/hour meter for gas models. One-year limited warranty.

| | | | | |
|--------------------|--------------------|-------------------------|--------------------|--------------------|
| Arbor Size | 1" (25 mm) | | | |
| Blade Capacity | 18" (457 mm) | | | |
| Depth of Cut | 6-5/8" (168 mm) | | | |
| L x W x H (inches) | 42" x 25" x 39" | | | |
| L x W x H (mm) | 1,067 x 635 x 991 | | | |
| Model | MK-1609H Standard | MK-1613H Standard | MK-1613H Premium | |
| Engine | Honda (Gas) | Honda (Gas) | Honda (Gas) | |
| Power | GX270* | GX390 Cyclone* | GX390 Cyclone* | |
| Weight | 210 lbs. (95 kg) | 223 lbs. (101 kg) | 233 lbs. (106 kg) | |
| Part# | 157867 | 160832 | 160772 | |
| Model | MK-1605B Premium | MK-1610B Premium | MK-1610B Premium | MK-1610B Premium |
| Engine | Baldor (Electric) | Baldor (Electric) | Baldor (Electric) | Honda (Electric) |
| Power | 5Hp 240V | 10Hp 240V 3 Phase‡ | 10Hp 240V 1 Phase‡ | 10Hp 480V 3 Phase‡ |
| Weight | 285 lbs. (129 kgs) | 415 lbs. (188 kg) | 380 lbs. (172 kg) | 415 lbs. (188 kg) |
| Part# | 168099 | 167426 | 168611 | 167427 |
| Optional | Lifting Bail | 6.5 Gallon Water Tank † | Tach/Hour Meter | |
| Part# | 157745 | 157852 | 153877 | |

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.

‡ Lifting bail required to mount water tank.

Blade not included.



Cast aluminum hinged blade guard



Positive-locking depth control mechanism



Optional water tank is available



Scan for Video



SRX-150H

SRX-150 Green Concrete Saw

Compact and lightweight, the SRX-150 dry cutting saw is engineered for early entry sawing of crack control joints within one to two hours of concrete finishing. The blade guard features a vacuum port to control dust when dry cutting. One year limited warranty.

| Model | SRX-150H | SRX-150K |
|--------------------|---------------------------|-------------------------|
| Engine | Honda GX160 Cyclone*(Gas) | CH255 Quad Clean* (Gas) |
| Starter | Pull | Pull |
| Horse Power | 4.8 | 5.5 |
| Blade Capacity | 6-3/8" (162 mm) | 6-3/8" (162 mm) |
| Depth of Cut | 1-1/8" (29 mm) | 1-1/8" (29 mm) |
| Arbor | Triangular | Triangular |
| L x W x H (inches) | 32" x 19" x 42" | 32" x 19" x 42" |
| L x W x H (mm) | 813 x 483 x 1,067 | 813 x 483 x 1,067 |
| Weight | 88 lbs. (39.9 kg) | 88 lbs. (39.9 kg) |
| Includes | Skid plate | Skid plate |
| Part# | 172023-H | 172023-K |



Anti-spall, quick change skid plate



Vacuum port for easy connection to dust control systems



Folding handle bar for compact transport and storage

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.
Blade not included.

Recommended Diamond Blades

GC-10 (purple)
Ultra Hard Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171934 |



GC-20 (green)
Hard Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171938 |



GC-30 (red)
Medium / Hard Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171282 |



GC-35 (orange)
Medium Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171959 |



GC-55 (yellow)
Medium / Soft Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171969 |



Skid plates sold separately. Replacement stainless steel skid plate part # 171286, replacement steel skid plate part # 171283. Blades fit Soff-Cut® saws without adapters.



SRX-2000H

SRX-2000 Green Concrete Saw

The self-propelled SRX-2000 dry cutting saw is engineered for early entry sawing of crack control joints within one to two hours of concrete finishing. The blade guard features a vacuum port to control dust when dry cutting. One year limited warranty.

| | | |
|--------------------|---------------------|---------------------|
| Model | SRX-2000H | SRX-2000HE |
| Engine | Honda (Gas) | Honda (Gas) |
| Starter | Pull | Electric |
| Power | GX-270 Cyclone* | GX-270 Cyclone* |
| Blade Capacity | 10" (254 mm) | 10" (254 mm) |
| Depth of Cut | 1-5/8" (41 mm) | 1-5/8" (41 mm) |
| Arbor | Triangular | Triangular |
| L x W x H (inches) | 82" x 24" x 43-1/2" | 82" x 24" x 43-1/2" |
| L x W x H (mm) | 2,083 x 610 x 1,105 | 2,083 x 610 x 1,105 |
| Weight | 286 lbs. (129.7 kg) | 295 lbs. (133.8 kg) |
| Includes | Skid plate | Skid plate |
| Part# | 172235 | 172235-E |



Anti-spall, quick change skid plate



Vacuum port for easy connection to dust control systems



Folding handle bar for compact transport and storage

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating. Blade not included.

Recommended Diamond Blades

GC-10 (purple)
Ultra Hard Aggregate

| Size | Part # |
|------|--------|
| 10" | 172620 |



GC-20 (green)
Hard Aggregate

| Size | Part # |
|------|--------|
| 10" | 171942 |



GC-30 (red)
Medium / Hard Aggregate

| Size | Part # |
|------|--------|
| 10" | 171953 |



GC-35 (orange)
Medium Aggregate

| Size | Part # |
|------|--------|
| 10" | 171963 |



GC-55 (yellow)
Medium / Soft Aggregate

| Size | Part # |
|------|--------|
| 10" | 171973 |



Skid plates sold separately. Replacement stainless steel skid plate part # 171287, replacement steel skid plate part # 171284. Blades fit Soff-Cut® saws without adapters.



CX-3® Walk-Behind Concrete Saw

The CX-3® Walk-Behind Concrete Saw is for small to medium jobs that require power and portability. This compact, lightweight saw has been engineered for maneuverability and reliability. The built-in water distribution system supplies water to both sides of the blade. Cuts within 1" of wall or curb. One-year limited warranty.

| | |
|---------------------------|-------------------|
| Model | CX-3® Honda |
| Engine | Honda (Gas) |
| Power | GX160 Cyclone* |
| Blade Capacity | 14" (356 mm) |
| Depth of Cut | 5-1/2" (140 mm) |
| Arbor Size | 1" (25 mm) |
| L x W x H (inches) | 32" x 19" x 42" |
| L x W x H (mm) | 813 x 483 x 1,067 |
| Weight | 116 lbs. (53 kg) |
| Part# | 159345 |

| | | | |
|-----------------|-------------------|------------|--------------|
| Optional | Water Tank System | Tachometer | Lifting Bail |
| Part# | 166784 | 153877 | 166781 |

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.
Blade not included.



Water connection for wet cutting and dust suppression



Hinged blade guard provides easy access for blade changes and inspection.



Folding handle bar for compact transport

Recommended Diamond Blades

AX-10 Premium Grade Asphalt

| Size | Part # |
|------|--------|
| 12" | 159617 |
| 14" | 159618 |



GX-10 Supreme Grade Green Concrete

| Size | Part # |
|------|--------|
| 12" | 159619 |
| 14" | 159620 |



CX-10 Premium Grade Cured Concrete

| Size | Part # |
|------|--------|
| 12" | 159615 |
| 14" | 159616 |



DX-10 Supreme Grade Cured Concrete

| Size | Part # |
|------|--------|
| 12" | 159685 |
| 14" | 159686 |

