



Blade not included  
MK-2014K

## MK-20 SERIES FEATURES

- One-piece box construction chassis made from 3/16" hot-rolled steel will not flex during operation
- Powder-coated chassis resists peeling & corrosion
- Cast-aluminum hinged blade guard
- Stainless steel water distribution system supplies water to both sides of blade
- Blade guard mounts on both left- or right-hand side of saw and cuts within 2" of wall or curb
- 1-3/16" blade shaft supported by two heavy-duty, self-aligning pillow block bearings
- Depth control assembly engineered for smooth, controlled blade insertion
- Built-in tach/hour meter
- Depth feed gauge indicator
- Heavy-duty hydro static transmission with variable speed drive
- Durable 8" x 2 1/4" non-slip rubber wheels with maintenance-free hubs & roller bearing
- Forward travel speed: 0-80'/minute

### Recommended Diamond Blades

**MK-505** *Supreme Grade*  
Cured Concrete

Size	Part #
18"	129072
20"	135301



**MK-615W** *Premium Grade*  
Asphalt over Concrete

Size	Part #
18"	150232
20"	154294



**MK-710W** *Supreme Grade*  
Asphalt

Size	Part #
18"	139089
20"	168006



**MK-762DMX** *Supreme Grade*  
General Purpose/Concrete

Size	Part #
18"	161295
20"	161296



1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | [www.mkdiamond.com](http://www.mkdiamond.com) | F 310.539.5158



<https://www.facebook.com/mkdiamondproducts>

[customerservice@mkdiamond.com](mailto:customerservice@mkdiamond.com)



<https://twitter.com/MKDiamond>



**MK Diamond Products, Inc.**



Blade not included

MK-2020HSP

## MK-20 Series Self-Propelled Concrete Saw

MK-20 Series of concrete saws combine innovation and engineering to produce one of the lightest, midsize self-propelled concrete saws available. Key to the design is the featured box frame and channel that produces a rigid frame, which helps reduce sawing-induced vibrations. Engine weight is evenly distributed over the blade shaft for added stability and tracking. Depth control assembly is engineered for smooth, controlled blade insertion. One-year limited warranty.

<b>Arbor Size</b>	1" (25 mm)			
<b>L x W x H (inches)</b>	46" x 26" x 37"			
<b>L x W x H (mm)</b>	1,168 x 660 x 940			
<b>Includes</b>	• Lifting Bail			
<b>Model</b>	MK-2013HE	MK-2013HSP	MK-2020HSP	MK-2024HSP
<b>Engine</b>	Honda (Gas)	Honda (Gas)	Honda (Gas)	Honda (Gas)
<b>Starter</b>	Electric	Pull	Electric	Electric
<b>Power</b>	GX390 Honda*	GX390 Cyclone*	GX630 V-Twin*	GX690 V-Twin*
<b>Blade Capacity</b>	18" (457 mm)	18" (457 mm)	20" (508 mm)	20" (508 mm)
<b>Depth of Cut</b>	6-5/8" (168 mm)	6-5/8" (168 mm)	7-5/8" (194 mm)	7-5/8" (194 mm)
<b>Weight</b>	290 lbs. (132 kg)	290 lbs. (132 kg)	392 lbs. (178 kg)	398 lbs. (181 kg)
<b>Part#</b>	155714	156499	156498	158777
<b>Optional</b>	6.5 Gallon Water Tank			
<b>Part#</b>	157852			

\*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.



Cast aluminum hinged blade guard



Blade guard mounts on either left- or right-hand side of saw and cuts within 2" of wall or curb



Easy to use control panel, includes built-in tach/hour meter.

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | [www.mkdiamond.com](http://www.mkdiamond.com) | F 310.539.5158

© 2017 MK Diamond Products, Inc. All Rights Reserved. Images and specifications are subject to change without notice. MK-20 Series Sell Sheet Part # 156996 (12/17)