



MK Diamond Products, Inc.



Blade not included

MK-3030K



MK-3000 SERIES FEATURES

- Totally enclosed and sealed blade shaft with continuous oil bath lubrication system
- Quick release, auto-latching bayonet mount blade guard
- Three position adjustable solid steel handlebars
- Blade guard uses “ride on the blade” water tubes for superior water delivery and blade cooling
- Saw designed for left or right side mounting of blade and blade guard
- Rigid frame front pointer with high visibility guide wheel for accurate tracking
- Instrumentation includes engine tach, fuel level and hour meter
- Ergonomic FNR traverse control
- Depth of cut indicator
- Blade guard has garden hose style connector for quick disconnecting
- Removable rear panel for easy service
- 7 rib powerband from engine to blade shaft
- Electric leadscrew for positive adjustment of cutting depth
- Wide front wheel base increases stability and allows ramp loading/unloading
- Eaton model 6 Hydrostatic transmission coupled to an MK trans-axle
- Meets EPA Interim Tier IV requirements

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customerservice@mkdiamond.com



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>



MK-3030K

MK-3000 Pro Gas Self-Propelled Concrete Saws

The MK-3000 series Concrete Saws are big performance saws in small packages. They have been engineered to take advantage of the new breed of high horsepower V-Twin air-cooled engines from Briggs, Stratton and Kohler. They provide the cutting depth and power of traditional street saws with all the advantages of a smaller, more maneuverable saw. The saws are fully self-propelled, like their big brother, the MK-4000, and use an electric lead-screw to raise and lower the blade. One-year limited warranty.

Starter	Electric					
Travel Speed	0-220 FPM Forward, 0-100 FPM Reverse					
Fuel Capacity	5.0 gallons					
Blade RPM	1,900					
Arbor	1" with 3/8" Drive Pin					
L x W x H (inches)	57" x 29¾" x 43"					
L x W x H (mm)	1,448 x 756 x 1,092					
Engine	Vanguard (Gas)			Kohler (Gas)		
Power	V-Twin Big Block OHV 35* (35 HP)			Command Pro CH980* (35 HP)		
Weight	650 lbs. (295 kg)			650 lbs. (295 kg)		
Model	MK-3020V	MK-3026V	MK-3030V	MK-3020K	MK-3026K	MK-3030K
Size	20" (508 mm)	26" (660 mm)	30" (762 mm)	20" (508 mm)	26" (660 mm)	30" (762 mm)
Depth of Cut	7-1/2" (190 mm)	10-1/2" (267 mm)	12-1/2" (318 mm)	7-1/2" (190 mm)	10-1/2" (267 mm)	12-1/2" (318 mm)
Part#	166447-20	166447-26	166447-30	166449-20	166449-26	166449-30

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.
Blade not included.