



Blade not included
MK-4036KB Kubota Saw

MK-4000 GAS/DIESEL SERIES FEATURES

- Totally enclosed and sealed blade shaft with continuous oil bath lubrication system
- Control set provides proportional blade raising/lowering and travel speed with one hand operation
- Quick release, auto-latching bayonet mount blade guard
- Blade guard uses "ride on the blade" water tubes for superior water delivery and blade cooling
- Eaton model 6 Hydrostatic transmission coupled to an MK differentiating trans-axle
- Saw designed for left or right side mounting of blade and blade guard
- Differential lock (for cutting on slippery surfaces) and free wheel/engage controls (to allow the saw to be pushed manually)
- Three-position adjustable solid steel handlebars
- Rigid frame front pointer with high visibility guide wheel for accurate tracking
- 7 rib power belt drive from engine to blade shaft
- Travel Speed: 0-220 FPM Forward, 0-100 FPM Reverse
- Fuel Capacity: 6 gallons
- Meets EPA and CARB requirements
- L x W x H: 64¼" x 34¾" x 47¼"

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customerservice@mkdiamond.com



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>



MK Diamond Products, Inc.



MK-4036KB Gas Kubota Saw 57Hp

MK-4000 Pro Series Self-Propelled Service Concrete Saws

The MK-4000 heavy-duty service Concrete Saw has been engineered for operator convenience, improved accessibility for maintenance and better control during operations. The MK-4000 has been designed for both front and rear pivoting and has easily removable rear and side panels to provide easy accessibility for maintenance. One-year limited warranty.

	Kubota (Gas) Water Cooled			
Engine	The 57Hp Kubota WG1605-G/L/N-E3 is a 4 cylinder in-line, gas fueled, naturally aspirated, liquid-cooled engine. It is fuel efficient, altitude compensating, has low emissions and meets EPA and CARB requirements. The engine is 1537cc in displacement. This engine offers very low vibration and is exceptionally quiet.			
Power	WG1605-G/L/N-E3* (57 Hp)			
Weight	1,080 lbs. (490 kg)			
Model	MK-4020KG	MK-4026KG	MK-4030KG	MK-4036KG
Blade Capacity	20" (508 mm)	26" (660 mm)	30" (762 mm)	36" (914 mm)
Blade RPM	2,200	1,900	1,650	1,350
Depth of Cut	7-1/2" (191 mm)	10-1/2" (267 mm)	12-1/2" (318 mm)	15" (381 mm)
Part#	172192-20	172192-26	172192-30	172192-36

	Kubota (Diesel) Water Cooled			
Engine	The 44Hp Kubota V1505-T-E3B is a 4 cylinder in-line, diesel fueled, turbo-charged, liquid-cooled engine. It is fuel efficient, altitude compensating, has low emissions and meets all EPA and CARB requirements. The engine is 1498cc in displacement and features Kubota's Three Vortec Combustion system, which produces an ideal air/fuel mixture that provides increased combustion efficiency and cleaner exhaust.			
Power	V1505-T-E3B* (44 Hp)			
Weight	1,080 lbs. (490 kg)			
Model	MK-4020KB	MK-4026KB	MK-4030KB	MK-4036KB
Blade Capacity	20" (508 mm)	26" (660 mm)	30" (762 mm)	36" (914 mm)
Blade RPM	2,300	2,000	1,750	1,450
Depth of Cut	7-1/2" (191 mm)	10-1/2" (267 mm)	12-1/2" (318 mm)	15" (381 mm)
Part#	167420-20	167420-26	167420-30	167420-36

Blade not included

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating?

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | www.mkdiamond.com | F 310.539.5158

© 2017 MK Diamond Products, Inc. All Rights Reserved. Images and specifications are subject to change without notice. MK-4000 Sell Sheet Part # AP080146 (03/17)