



**MK Diamond Products, Inc.**



Blade not included.

## **MK-3000B ELECTRIC SERIES FEATURES**

- Totally enclosed and sealed blade shaft with continuous oil bath lubrication system
- Quick release, auto latching bayonet mount blade guard
- Three position adjustable solid steel handle bars
- Blade guard uses "ride on the blade" water tubes for superior water delivery and blade cooling
- Saw designed for left or right side mounting of blade and blade guard
- Ergonomic FNR traverse control
- Transmission can be disengaged from axle to allow saw to be pushed manually
- Depth of cut indicator
- Blade guard has garden hose style connector for quick disconnecting
- Removable rear and lower front panel for easy service
- 7 rib powerband from engine to blade shaft
- Electric leadscrew for positive adjustment of cutting depth
- Wide front wheel base increases stability and allows ramp loading/unloading
- Eaton model 6 Hydrostatic transmission coupled to an MK trans-axle

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

[www.mkdiamond.com](http://www.mkdiamond.com) | [customerservice@mkdiamond.com](mailto:customerservice@mkdiamond.com)



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>



Blade not included.

## MK-3000B Pro Electric Self-Propelled Concrete Saws

The MK-3000 Electric Saw provides a solution for those environments and situations where electric power is the right choice, whether for indoor use or simply operator preference. The saw utilizes a three-phase, 20 Hp, Baldor electric motor in 230V or 460V to match the user's need. The saw features the same raise/lower system, self-propelled transmission and control set as other MK-3000s. An ammeter is provided to help monitor load when cutting. One-year limited warranty.

Switch	IP 65 IEC Across the line starter			
Travel Speed	0-220 FPM Forward, 0-100 FPM Reverse			
Arbor	1" with 3/8" dirve pin			
L x W x H (inches)	57" x 29 3/4" x 43"			
L x W x H (mm)	1,448 x 756 x 1,092mm			
Motor	Baldor (Electric)			
Weight	700 lbs. (318kg)			
Model	MK-3020B	MK-3020B	MK-3026B	MK-3026B
Size	20" (508mm)	20" (460mm)	26" (660mm)	26" (660mm)
Power	20 Hp 230V 3Ph	20 Hp 460V 3Ph	20 Hp 230V 3Ph	20 Hp 460V 3Ph
Blade RPM	2,580	2,580	2,030	2,030
Depth of Cut	7-1/2" (191mm)	7-1/2" (191mm)	10-1/2" (267mm)	10-1/2" (267mm)
Part#	167428-20	167429-20	167428-26	167429-26

Model	MK-3030B	MK-3030B
Size	30" (762mm)	30" (762mm)
Power	20 Hp 230V 3Ph	20 Hp 460V 3Ph
Blade RPM	1,680	1,680
Depth of Cut	12-1/2" (318mm)	12-1/2" (318mm)
Part#	167428-30	167429-30

Blade not included.



Baldor 20HP, 3 Phase, TEFC motor, providing 30ft-lb of torque



Three position adjustable solid steel handle bars



7 rib powerband from engine to center shaft

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | www.mkdiamond.com | F 310.539.5158

© 2017 MK Diamond Products, Inc. All Rights Reserved. Images, prices and specifications are subject to change without notice. MK-3000B Electric Series Sell Sheet Part # AP080162 (02/17)