



Blade not included
MK-5005S

MK-5000 ELECTRIC SERIES FEATURES

- Precision screw feed mechanism allows the cutting head to be easily raised or lowered to the precise cutting depth required
- Self-leveling blade guard provides optimum blade coverage for operator safety
- Open-back design allows for material up to 20" long to be cut
- Conveyor cart built from heavy-duty cast aluminum
- 3 phase saws are equipped with GE NEMA 1 starters in NEMA 12 enclosure
- Adjustable water supply for maximum blade protection
- Built-in tie-downs for safer saw transport
- Ergonomically designed handle for reduced operator fatigue
- Heavy-duty built-in forklift brackets allow lift to approach from the front or either side of the saw
- One-year limited warranty

Recommended Diamond Blades

MK-62GSPV *Pro Granite Silent Core*

Size	Part #
14"	154591
20"	155902



MK-925DSLX *Supreme Hard Material Silent Core*

Size	Part #
14"	161283
20"	160971



1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customerservice@mkdiamond.com



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>



Blade not included



MK-5000 ELECTRIC SERIES Wet Cutting Block Saws

The MK-5000 Series of block saws set the quality standard for durability and maintenance-free operation. These saws are specially designed to provide the highest level of productivity, operator safety and convenience. Heavy-duty cast aluminum and steel parts ensure the finest value in the masonry and stone industry. One-year limited warranty.

Motor	Baldor (Electric)
Length of Cut	20" (508 mm)
L x W x H (inches)	53" x 26" x 63"
L x W x H (mm)	1,346 x 660 x 1,600
Includes	• Electric Water Pump • Rip Guide

Model	MK-5005S		MK-5005T		MK-5007T		
Power	5 Hp, 1PH		5 Hp, 3PH		7.5 Hp, 3PH		
Weight	445 lbs. (202 kg)		451 lbs. (205 kg)		485 lbs. (220 kg)		
Blade Guard	14"	20"	14"	20"	14"	20"	24"
Depth of Cut	5" (127 mm)	8" (203 mm)	5" (127 mm)	8" (203 mm)	5" (127 mm)	8" (203 mm)	10" (254 mm)
208-230V Part#	160634-14	160634	160636-14	160636	160641-14	160641	160641-24
460V Part#	-	-	160637-14	160637	160642-14	160642	160642-24

Model	MK-5010S		MK-5010T		MK-5009T		
Power	10 Hp, 1PH		10 Hp, 3PH		9 Hp, 3PH		
Weight	503 lbs. (228 kg)		503 lbs. (228 kg)		503 lbs. (288 kg)		
Blade Guard	24"		24"		14"	20"	24"
Depth of Cut	10" (254 mm)		10" (254 mm)		5" (127 mm)	8" (203 mm)	10" (254 mm)
208-230V Part#	169328		169330		160646-14	160646	160646-24
460V Part#	-		169331		160647-14	160647	160647-24
575V Part#	-		-		-	-	-

(Motor available in other electrical configurations.)



Heavy-duty cast aluminum conveyor cart



Foot pedal for hands-free cutting head operation



Open-back design allow for materials up to 20" long to be cut

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | www.mkdiamond.com | F 310.539.5158

© 2017 MK Diamond Products, Inc. All Rights Reserved. Images and specifications are subject to change without notice. MK-5000 Sell Sheet Part # AP080147 (04/17)